

15902.02

Swi plus

Swi Plus compact projector adjustable emission.


Available with optics for medium or large beam emission.

24V electronic driver to be ordered separately.


02 black



novalux
ITALIAN LIGHTING STYLE SINCE 1948



D: 60 mm
H: 74 mm



Material

Body made of anodized powder coated aluminium alloy bracket made of AISI 316L stainless steel; screws made of stainless steel flat screen made of transparent extra-clear tempered glass.

Wiring

Complete with cord grip made of nickel-plated brass and hydrophobic membrane GORE-TEX and with H05RN-F L=500mm power supply cable separated, electronic stabilized driver.

Supply voltage: 24Vdc, 220-240V 50/60Hz

Photobiological Risk

Certified device in RISK GROUP 1 (Low Risk) - The lamp does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010.

Compliance

In accordance with standard: CEI EN 60598-1:2008 + A11:2009, IEC 60598-2-2, 60598-2-13.

Sources

Color: white

Power: 6W

Color temperature: 3000K

CRI: >80

Nominal flux (Tc=25°C): 620 lm

Lifespan (Ta=25°C): 50000h L70

Lamp included

Photometric data


Luminous flux (Ta=25°C): 514 lm

Beamwidth: 60°


15902.02 Swi plus

Swi Plus compact projector adjustable emission.


Accessories




E924K0010KK
Electronic
stabilized driver
24Vdc max 10W




E924K0100KK
Electronic
stabilized driver
24Vdc 96W max
IP67




E924K0035KK
Electronic
stabilized driver
24Vdc max 35W



E924K0075KK
Electronic
stabilized driver
24Vdc max 75W



E924K1100KK
Electronic
stabilized driver
24Vdc 96W max



A830K0001KK
Spike for
installation in the
ground