




Lines | 100-264 V | topLED 15 W 350 mA | Modular | CRI 80
63605



43 x
1005



Technical data	
Collection	tråddel
Installation position	Wall lights - Ceiling
Installation environment	Indoor
Light Source	LED
Circuit structure	topLED
Optic	Diffused
Power	15 W
Luminous flux (source)	2020 lm
Frequency	50 - 60 Hz
CCT / Tonalità	3000 K
Colour rendering index	80 Ra
AC / DC	AC-DC
Safety class	1
IP	IP40
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Yes
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing casing	
Material	Aluminium
Colour	Aluminium
Processing	Open-pore anodisation

Finishing diffuser	
Material	PC
Colour	opaline



Lines | 100-264 V | topLED 15 W 350 mA | Modular | CRI 80
63605

Single emission lines for indoor application. The warm white LED light source with a diffused light distribution is composed of 130 topLEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 2020 lm, with a 134.7 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a aluminium finish, processed by means of open-pore anodisation; the diffuser is made of PC. The ingress protection degree is IP40; the total weight is of 1.93 kg. The power supply driver is included in the delivery.

The total absorbed power is 15 W.

The device features protection class I and can be wall lights or ceiling-mounted, with a 43 x 43 mm hole (in plasterboard).

Illuminotechnical Features

Luminous flux (source)	2020 lm
Colour temperature	3000 K
Colour rendering index	80 Ra



Giunzione

Code

62180




Connettore

Cable gland: no; colors: nero.

Code

60127



Tappo

Code

63601