



222

SPIKE



LED



LED



LED



LED

DISPONIBILE DA
GIUGNO
AVAILABLE FROM
JUNE

Mini proiettore orientabile LED IP65. Sorgenti LED warm white 3000K.

MATERIALI

Corpo, staffa e picchetto in lega di alluminio anodizzata e verniciata a polvere; viteria in acciaio inox; schermo piano in vetro temprato extrachiaro trasparente; modulo LED e alimentazione integrata, interamente impregnati in resina ottica trasparente.

CABLAGGIO

Fornito di cavo di alimentazione H05RN-F 2x0,75mm² L=1000mm; alimentazione elettronica 220-240V 50/60Hz integrata.

LED IP65 adjustable compact projector. LED sources warm white 3000K.

MATERIALS

Body, bracket and spike made of anodized powder coated aluminium alloy; screws made of stainless steel; flat screen made of transparent extra-clear tempered glass; LED module and integrated power entirely resin soaked.

WIRING

Complete with H05RN-F 2x0,75mm² L=1000mm power supply cable. Integrated electronic 220-240V 50/60Hz driver.

SPIKE LED mini proiettore orientabile; alimentatore elettronico incluso.
SPIKE LED compact projector adjustable; electronic driver included.

3000 K

Codice/Code	W led	Fascio/Beam	Flusso apparecchio (lm) Fixture flux (lm)
101201.02	5	38°	480



■ _02 - Nero/Black

