



0596 Smart S 05967CE1E

Application Area

indoor

Description

Cutting hole



100mm

Lamp specification

Subcategory: Advanced

Generation: D1

LES: SAM 15

MacAdam: 3

Color temp.: 3000K

IRC/CRI: IRC >90

Nominal luminous flux: 2125lm

Beam Angle: 20°

Wiring Specification

Driver standard

220-240V 50-60Hz 500mA

Power 17W

Construction specifications

Body: Die-cast aluminium body

Optic: Polycarbonate lens diffuser

Color: White

Painting:

TA max: 30°

Photobiological safety: 1

IP rate: 20

Glow wire: 850°





Ilmas S.p.A.
Via Vittorio Veneto, 23b
20010 Bernate Ticino (MI)
P. Iva: IT 04095080158



tel. +39 02 93900 349
tel. +39 02 93900 353
fax. +39 02 93900 357



<http://www.ilmas.com>
ilmas@ilmas.com

Duration: 50.000h

Weight: 0.35kg

Accessories

ilmas

0596 Smart S 059616

ilmas

0596 Smart S 059614

ilmas

0596 Smart S 059618

ilmas

0596 Smart S 059613

ilmas

0596 Smart S 9000B93

ilmas

0596 Smart S 059615

ilmas

0596 Smart S 059617

ilmas

0596 Smart S 059611

ilmas

0596 Smart S 9000B91

ilmas

0596 Smart S 059610

ilmas

0596 Smart S 0596Ape