

# mira 65

# LED

powered by  
Seoul® Semiconductor Z5M



simmetrico  
symmetric  
symétriques  
simétrico  
symmetrisch



asimmetrico  
asymmetric  
asymétriques  
asimétrico  
asymmetrisch

example code:

art.	LED	○	anodized
5321	LS5	N	inx

art.  
**5321**  
**5322**

design Ufficio Tecnico Landa


corpo alluminio estruso  
anodizzato  
body in extruded  
aluminium  
corps en aluminium extrudé  
anodisé  
cuerpo en aluminio  
extrusionado y anodizado  
Körper aus eloxiertem  
fließgepresst Aluminium

diffusore vetro trasparente  
e opale  
diffuser glass transparent  
and opal  
diffuser verre transparent  
et opale  
difusor vidrio transparente  
y ópalo  
Diffuser Glas klar und opal

32 RECESSED



5321



code ....LS5



5321





code ....LL5



5321



code ....L5



FOR TECHNICAL DETAILS VISIT  
[www.landa.it](http://www.landa.it)

IP67

art.	LUX 1mt	art.	LUX 1mt	art.	LUX 1mt	W	V	Type	⚡	Ra
5321LS5N3740	10°	5321LL5N	700	5321L5N	124	5	24	4000K	480LM	80
5321LS5H3740		5321LL5H	700	5321L5H	124			3000K	480LM	80

ELECTRIFICATION

# LED

dettagli / details / details  
detales / details:  
p.A54 - A55

Energy efficiency classes

Trasformer available:

cod. 0409BT014 to connect up to **2** pieces – GE LIGHTING IP67 24V c.c. 12W  
cod. 0409BT015 to connect up to **4** pieces – GE LIGHTING IP67 24V c.c. 25W

Trasformer on request:

cod. 0409BT016 to connect up to **16** pieces – GE LIGHTING IP67 24V c.c. 100W

A++ ÷ A

mira 65 (24V)

Projectors  
**NEW**  
Recessed

Contemporary

Traditional

Thanks to MP Illumination - GR




RECESSED


33



5322



code ....L5




...brz



...inx

art.		W	V	Type		Ra
5322L5N		5	24	4000K 480LM		80
5322L5H		5	24	3000K 480LM		80



Accessories on request:



code 0404M009  
Single connection IP68

