

tubo



LED
powered by
Liteon® Optoelectronics

simmetrico
symmetric
symétriques
simétrico
symmetrisch








example code:
| art. | size | LED |  |
6001 .0500 L10 H

art.
6001
6002

design Ufficio Tecnico Landa



single connection
2 Mt. cable
-05RN-F
included

art.			°C	W	V	Type		Ra
6001.0500L10N		150°	25	10	24 c.c.	4000K 1200LM	80	
6001.0500L10H						3000K 1050LM	80	
6001.1000L20N		150°	25	20	24 c.c.	4000K 2400LM	80	
6001.1000L20H						3000K 2100LM	80	

CONTEMPORARY

50

corpo alluminio estruso
anodizzato e policarbonato
trasparente

body in extruded anodized
aluminium and transparent
polycarbonate



corps en aluminium extrudé
anodisé et polycarbonate
transparent

cuerpo en aluminio
extrusionado y anodizado y
policarbonato transparente








Körper aus eloxiertem
fließgepresst Aluminium und
Polykarbonat klar

diffusore policarbonato opale
diffuser opal polycarbonate
diffuser polycarbonate opale
difusor policarbonato ópalo
Diffuser Polykarbonat opal

 24V c.c.



loop in loop out connection
2x2 Mt. cable
-05RN-F
included

art.			°C	W	V	Type		Ra
6002.0500L10N		150°	25	10	24 c.c.	4000K 1200LM	80	
6002.0500L10H						3000K 1050LM	80	
6002.1000L20N		150°	25	20	24 c.c.	4000K 2400LM	80	
6002.1000L20H						3000K 2100LM	80	

FOR TECHNICAL DETAILS VISIT
www.landa.it

IP67

ELECTRIFICATION

LED

dettagli / details / details
détalles / details:
p.A52-A53

Energy efficiency classes

Trasformer available:

cod. 0409BT014 – GE LIGHTING IP67 24V c.c. 12W
cod. 0409BT015 – GE LIGHTING IP67 24V c.c. 25W

Trasformer on request:

cod. 0409BT016 – GE LIGHTING IP67 24V c.c. 100W

A++ ÷ A

Accessories on request:



code **0404M011**
Single connection IP68



Projectors

Recessed

NEW

Contemporary

Traditional

CONTEMPORARY




Accessories:




00A6001.01





00A6001.02



00A6001.03



00A6001.04



00A6001.05



tubo

LED
powered by
Liteon® Optoelectronics

simmetrico
symmetric
symétriques
simétrico
symmetrisch

example code:
| art. | size | LED | ○ |
6011 .1000 L20 | N |

art.
6011
6012

design Ufficio Tecnico Landa

corpo alluminio estruso
anodizzato e policarbonato
trasparente

body in extruded anodized
aluminium and transparent
polycarbonate

corps en aluminium extrudé
anodisé et polycarbonate
transparent

cuerpo en aluminio
extrusionado y anodizado y
policarbonato transparente

52

Körper aus eloxiertem
fließgepresst Aluminium und
Polykarbonat klar

diffusore policarbonato
trasparente



diffuser transparent
polycarbonate

diffuser polycarbonate
transparent

difusor policarbonato
transparente



Diffuser Polykarbonat klar

III 24V c.c.



single connection
2 Mt. cable
-05RN-F
included

art.		°C	W	V	Type	Ⓛ	Ra	
6011.0500L10N	○	150°	25	10	24 c.c.	4000K	1200LM	80
6011.0500L10H	○					3000K	1050LM	80
6011.1000L20N	○	150°	25	20	24 c.c.	4000K	2400LM	80
6011.1000L20H	○					3000K	2100LM	80



loop in loop out connection
2x2 Mt. cable
-05RN-F
included

FOR TECHNICAL DETAILS VISIT
www.landa.it

IP67

art.		°C	W	V	Type	Ⓛ	Ra	
6012.0500L10N	○	150°	25	10	24 c.c.	4000K	1200LM	80
6012.0500L10H	○					3000K	1050LM	80
6012.1000L20N	○	150°	25	20	24 c.c.	4000K	2400LM	80
6012.1000L20H	○					3000K	2100LM	80

ELECTRIFICATION

LED

dettagli / details / details
détalles / details:
p.A52-A53

Energy efficiency classes

Trasformer available:

cod. 0409BT014 – GE LIGHTING IP67 24V c.c. 12W

cod. 0409BT015 – GE LIGHTING IP67 24V c.c. 25W

Trasformer on request:

cod. 0409BT016 – GE LIGHTING IP67 24V c.c. 100W

A++ ÷ A

Accessories on request:



code 0404M011
Single connection IP68

Projectors

Recessed

NEW

Contemporary

Traditional

CONTEMPORARY




Accessories:




00A6001.01




00A6001.02



00A6001.03



00A6001.04



00A6001.05

