

F.

Brick

IP65

IK08

WALL EFFECT LIGHT
Diffused reflector
Single - double emission



Collection name

BRICK

BRICK

BRICK

BRICK

Technical data

Power (Real data)	7.0 W	14.0 W	2 x 10.0 W	2 x 10.0 W
Lumen 3000K (Real data)	507 lm (Optic .07)	1014 lm (Optic .07)	1217 lm (Optic .05)	1434 lm (Optic .05)
Lumen 4000K (Real data)	523 lm (Optic .07)	1045 lm (Optic .07)	1229 lm (Optic .05)	1577 lm (Optic .05)
Class	I	I	I	I
Nominal Voltage	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz
Power supply	Included	Included	Included	Included
Openings	Single emission	Single emission	Double emission	Double emission

Configuration code

Select finish / led / optic

30801 + X + Y + Z

30802 + X + Y + Z

30806 + X + Y + Z

30807 + X + Y + Z

Finish X

- 1 - Anthracite gloss 8-10
- 2 - White (RAL 9010)
- 4 - Grey (RAL 9006)
- 8 - Dark brown

- 1 - Anthracite gloss 8-10
- 2 - White (RAL 9010)
- 4 - Grey (RAL 9006)
- 8 - Dark brown

- 1 - Anthracite gloss 8-10
- 2 - White (RAL 9010)
- 4 - Grey (RAL 9006)
- 8 - Dark brown

- 1 - Anthracite gloss 8-10
- 2 - White (RAL 9010)
- 4 - Grey (RAL 9006)
- 8 - Dark brown

Color LED Y

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

Optic Z

- .07 - Wall washer
- .05 - Diffused

- .07 - Wall washer
- .05 - Diffused

- .05 - Diffused

- .05 - Diffused

Technical drawing

