

Brick

IK08 IP65

WALL EFFECT LIGHT
Comfort concentrated reflector
Single emission



Collection name

BRICK

BRICK

Technical data

Power (Real data)	4.7 W	9.4 W
Lumen 3000K (Real data)	336 lm (Optic .01)	670 lm (Optic .01)
Lumen 4000K (Real data)	346 lm (Optic .01)	691 lm (Optic .01)
Class	I	I
Nominal Voltage	220-240V 50/60Hz	220-240V 50/60Hz
Power supply	Included	Included
Openings	Single emission	Single emission

Configuration code

Select finish / led / optic

30803 + X + Y + Z

30804 + X + Y + Z

Finish X

- 1 - Anthracite gloss 8-10
- 2 - White (RAL 9010)
- 4 - Grey (RAL 9006)

- 1 - Anthracite gloss 8-10
- 2 - White (RAL 9010)
- 4 - Grey (RAL 9006)

Color LED Y

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

Optic Z

- .01 - 10° Spot
- .02 - 30° Medium

- .01 - 10° Spot
- .02 - 30° Medium

Technical drawing

