

F.

IP65

IK08

Pin

WALL EFFECT LIGHT
White led



Collection name

PIN

PIN

PIN

PIN

Technical data

Power (Real data)	13.0 W	2 x 13.0 W	10.0 W	10.0 W
Lumen 3000K (Real data)	1005 lm (Optic .05)	2 x 1005 lm (Optic .05)	333 lm (Optic .05)	2 x 419 lm (Optic .05)
Lumen 4000K (Real data)	1036 lm (Optic .05)	2 x 1036 lm (Optic .05)	343 lm (Optic .05)	2 x 432 lm (Optic .05)
Class	I	I	I	I
Nominal Voltage	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz
Power supply	Included	Included	Included	Included
Openings	Single emission	Double emission	Single emission	Double emission

Configuration code

Select finish / led / optic

31001 + X + Y + Z

31022 + X + Y + Z

31002 + X + Y + Z

31023 + X + Y + Z

Finish **X**

- 1 - Anthracite gloss 8-10
- 2 - White (RAL 9010)
- 4 - Grey (RAL 9006)
- 8 - Dark brown

- 1 - Anthracite gloss 8-10
- 2 - White (RAL 9010)
- 4 - Grey (RAL 9006)
- 8 - Dark brown

- 1 - Anthracite gloss 8-10
- 2 - White (RAL 9010)
- 4 - Grey (RAL 9006)
- 8 - Dark brown

- 1 - Anthracite gloss 8-10
- 2 - White (RAL 9010)
- 4 - Grey (RAL 9006)
- 8 - Dark brown

Color LED **Y**

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

Optic **Z**

- .05 - Diffused

- .05 - Diffused

- .05 - Diffused

- .05 - Diffused

Technical drawing

