

# F.

# Mini Slim

IP66

IK08

WALL EFFECT LIGHT  
Diffused reflector



## Collection name

MINI SLIM

MINI SLIM

MINI SLIM

MINI SLIM

## Technical data

Power (Real data)	11 W	7.8 W	2 x 11.0 W	2 x 7.8 W
Lumen 3000K (Real data)	959 lm (Optic .07)	503 lm (Optic .05)	2 x 959 lm (Optic .07)	2 x 503 lm (Optic .05)
Lumen 4000K (Real data)	974 lm (Optic .07)	518 lm (Optic .05)	2 x 974 lm (Optic .07)	2 x 518 lm (Optic .05)
Class	I	I	I	I
Nominal Voltage	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz
Power supply	Included	Included	Included	Included
Openings	Single emission	Single emission	Double emission	Double emission

## Configuration code

### Select finish / led / optic

30901 + X + Y + Z

30904 + X + Y + Z

30923 + X + Y + Z

30926 + X + Y + Z

Finish X

- 1 - Anthracite gloss 8-10
- 2 - White (RAL 9010)
- 4 - Grey (RAL 9006)
- 8 - Dark brown

- 1 - Anthracite gloss 8-10
- 2 - White (RAL 9010)
- 4 - Grey (RAL 9006)
- 8 - Dark brown

- 1 - Anthracite gloss 8-10
- 2 - White (RAL 9010)
- 4 - Grey (RAL 9006)
- 8 - Dark brown

- 1 - Anthracite gloss 8-10
- 2 - White (RAL 9010)
- 4 - Grey (RAL 9006)
- 8 - Dark brown

Color LED Y

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

Optic Z

- .07 - Wall washer

- .05 - Diffused

- .07 - Wall washer

- .05 - Diffused

## Technical drawing

