

Slim

WALL EFFECT LIGHT
Diffused & concentrated reflector

IK08 IP66



Collection name	SLIM	SLIM	SLIM
Technical data			
Power (Real data)	20.0 W	20.0 W	22.0 W
Lumen 3000K (Real data)	1452 lm (Optic .06)	1481 lm (Optic .06)	3317 lm (Optic .01)
Lumen 4000K (Real data)	1512 lm (Optic .06)	1541 lm (Optic .06)	3469 lm (Optic .01)
Class	I	I	I
Nominal Voltage	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz
Power supply	Included	Included	Included
Openings	Single emission	Double emission	Single emission
Configuration code			
Select finish / led / optic	30945 + X + Y + Z	30946 + X + Y + Z	30947 + X + Y + Z
Finish X	<ul style="list-style-type: none"> 1 - Anthracite gloss 8-10 2 - White (RAL 9010) 4 - Grey (RAL 9006) 8 - Dark brown 	<ul style="list-style-type: none"> 1 - Anthracite gloss 8-10 2 - White (RAL 9010) 4 - Grey (RAL 9006) 8 - Dark brown 	<ul style="list-style-type: none"> 1 - Anthracite gloss 8-10 2 - White (RAL 9010) 4 - Grey (RAL 9006) 8 - Dark brown
Color LED Y	<ul style="list-style-type: none"> .2 - 2700K CRI > 80 .3 - 3000K CRI > 80 .4 - 4000K CRI > 80 	<ul style="list-style-type: none"> .2 - 2700K CRI > 80 .3 - 3000K CRI > 80 .4 - 4000K CRI > 80 	<ul style="list-style-type: none"> .2 - 2700K CRI > 80 .3 - 3000K CRI > 80 .4 - 4000K CRI > 80
Optic Z	<ul style="list-style-type: none"> .06 - Asymmetric .07 - Wall washer 	<ul style="list-style-type: none"> .06 - Asymmetric 	<ul style="list-style-type: none"> .01 - 10° Spot .36 - 25° Medium .32 - 45° Wide .38 - 10°x40° Elliptical .07 - Wall washer
Technical drawing			