

Mok

WALL EFFECT LIGHT
Comfort concentrated reflector

IK08

IP65



Collection name

MOK

MOK

Technical data

Power (Real data)	18.0 W	2 x 18.0 W
Lumen 3000K (Real data)	1975 lm (Optic .11)	2 x 1975 lm (Optic .11)
Lumen 4000K (Real data)	2037 lm (Optic .11)	2 x 2037 lm (Optic .11)
Class	I	I
Nominal Voltage	220-240V 50/60Hz	220-240V 50/60Hz
Power supply	Included	Included
Openings	Single emission	Double emission









Configuration code

Select finish / led / optic







32024 + X + Y + Z

32027 + X + Y + Z

Finish X

- | | | | |
|---|---------------------------|---|---------------------------|
|  | 1 - Anthracite gloss 8-10 |  | 1 - Anthracite gloss 8-10 |
|  | 2 - White (RAL 9010) |  | 2 - White (RAL 9010) |
|  | 4 - Grey (RAL 9006) |  | 4 - Grey (RAL 9006) |
|  | 8 - Dark brown |  | 8 - Dark brown |

Color LED Y

- | | | | |
|---|---------------------|---|---------------------|
|  | .2 - 2700K CRI > 80 |  | .2 - 2700K CRI > 80 |
|  | .3 - 3000K CRI > 80 |  | .3 - 3000K CRI > 80 |
|  | .4 - 4000K CRI > 80 |  | .4 - 4000K CRI > 80 |

Optic Z

- | | | | |
|---|------------------|---|------------------|
|  | .11 - 12° Spot |  | .11 - 12° Spot |
|  | .12 - 24° Medium |  | .12 - 24° Medium |
|  | .13 - 38° Medium |  | .13 - 38° Medium |

Technical drawing

