

Round

IP67 IK08

RECESSED DOWNLIGHT
White led



Collection name

ROUND

ROUND

ROUND

Technical data

Power (Real data)	18.0 W	18.0 W	18.0 W
Lumen 3000K (Real data)	1975 lm (Optic .05)	2075 lm (Optic .27)	2102 lm (Optic .07)
Lumen 4000K (Real data)	2037 lm (Optic .05)	2140 lm (Optic .27)	2167 lm (Optic .07)
Class	I	I	I
Nominal Voltage	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz
Power supply	Included	Included	Included

Configuration code

Select finish / led / optic

20723 + X + Y + Z

20730 + X + Y + Z

20731 + X + Y + Z

Finish X

- 2 - White (RAL 9010)
- 4 - Grey (RAL 9006)
- 6 - Inox Aisi 316L

- 2 - White (RAL 9010)
- 4 - Grey (RAL 9006)
- 6 - Inox Aisi 316L

- 2 - White (RAL 9010)
- 4 - Grey (RAL 9006)
- 6 - Inox Aisi 316L

Color LED Y

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

Optic Z

- .05 - Diffused
- .11 - 12° Spot
- .12 - 24° Medium
- .13 - 38° Medium

- .27 - Symmetric

- .07 - Wall washer

Technical drawing

