

F.

IP65

IK07

Pin

SQUARE BOLLARD
4 Openings



Collection name

PIN 245 mm

PIN 605 mm

Technical data

Power (Real data)	4.5 W
Lumen 3000K (Real data)	325 lm (Optic .14)
Lumen 4000K (Real data)	335 lm (Optic .14)
Class	I
Nominal Voltage	220-240V 50/60Hz
Power supply	Included
Openings	4 openings

Power (Real data)	4.5 W
Lumen 3000K (Real data)	325 lm (Optic .14)
Lumen 4000K (Real data)	335 lm (Optic .14)
Class	I
Nominal Voltage	220-240V 50/60Hz
Power supply	Included
Openings	4 openings

Configuration code

Select finish / led / optic

61003 + X + Y + Z

61027 + X + Y + Z

Finish **X**

- 1 – Anthracite gloss 8-10
- 4 – Grey (RAL 9006)
- 8 – Dark brown
- .2 – 2700K CRI > 80
- .3 – 3000K CRI > 80
- .4 – 4000K CRI > 80
- .14 – Transparent

- 1 – Anthracite gloss 8-10
- 4 – Grey (RAL 9006)
- 8 – Dark brown
- .2 – 2700K CRI > 80
- .3 – 3000K CRI > 80
- .4 – 4000K CRI > 80
- .14 – Transparent

Color LED **Y**

Optic **Z**

Technical drawing



Isolux diagrams

