

# F.

IP65

IK09

# Step

BOLLARD  
h. 330 mm



## Collection name

STEP 330 mm

STEP 330 mm

STEP 330 mm

## Technical data

Power (Real data)	24.0 W
Lumen 3000K (Real data)	285 lm (Optic .14)
Lumen 4000K (Real data)	310 lm (Optic .14)
Class	I
Nominal Voltage	220-240V 50/60Hz
Power supply	Included
Openings	1 opening

Power (Real data)	24.0 W
Lumen 3000K (Real data)	675 lm (Optic .14)
Lumen 4000K (Real data)	734 lm (Optic .14)
Class	I
Nominal Voltage	220-240V 50/60Hz
Power supply	Included
Openings	2 openings

Power (Real data)	24.0 W
Lumen 3000K (Real data)	954 lm (Optic .14)
Lumen 4000K (Real data)	1004 lm (Optic .14)
Class	I
Nominal Voltage	220-240V 50/60Hz
Power supply	Included
Openings	4 openings

## Configuration code

### Select finish / led / optic

61901 + X + Y + Z

61923 + X + Y + Z

61945 + X + Y + Z

Finish X

- 1 - Anthracite gloss 8-10
- 4 - Grey (RAL 9006)
- 8 - Dark brown

- 1 - Anthracite gloss 8-10
- 4 - Grey (RAL 9006)
- 8 - Dark brown

- 1 - Anthracite gloss 8-10
- 4 - Grey (RAL 9006)
- 8 - Dark brown

Color LED Y

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80




Optic Z

- .14 - Transparent

- .14 - Transparent

- .14 - Transparent

## Technical drawing



## Isolux diagrams

