

# F.

# Line

IP67

IK09

IK08

RECESSED LIGHT  
White led  
Comfort concentrated reflector



## Collection name

LINE 295 mm

LINE 535 mm

LINE 970 mm

LINE 1270 mm

## Technical data

Power (Real data)	12.0 W	24.0 W	30.0 W	40.0 W
Lumen 3000K (Real data)	1442 lm (Optic .01)	2958 lm (Optic .01)	3667 lm (Optic .01)	5238 lm (Optic .01)
Lumen 4000K (Real data)	1525 lm (Optic .01)	3217 lm (Optic .01)	3860 lm (Optic .01)	5514 lm (Optic .01)
Class	I (Class II on request)	I (Class II on request)	I (Class II on request)	I (Class II on request)
Nominal Voltage	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz
Power supply	Included	Included	Included	Included
Max load (Alu version)	1000 kg (Alu, walk over)	1000 kg (Alu, walk over)	1000 kg (Alu, walk over)	1000 kg (Alu, walk over)
Max load (Inox version)	1500 kg (Inox, walk over)	1500 kg (Inox, walk over)	1500 kg (Inox, walk over)	1500 kg (Inox, walk over)

## Configuration code

### Select finish / led / optic

10601 + X + Y + Z

10602 + X + Y + Z

10603 + X + Y + Z

10604 + X + Y + Z

Finish X

- 4 - Grey (RAL 9006)
- 6 - Inox Aisi 316L

- 4 - Grey (RAL 9006)
- 6 - Inox Aisi 316L

- 4 - Grey (RAL 9006)
- 6 - Inox Aisi 316L

- 4 - Grey (RAL 9006)
- 6 - Inox Aisi 316L

Color LED Y

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

Optic Z

- .01 - 10° Spot
- .36 - 25° Medium
- .32 - 45° Wide
- .38 - 10°x40° Elliptical
- .07 - Wall washer

- .01 - 10° Spot
- .36 - 25° Medium
- .32 - 45° Wide
- .38 - 10°x40° Elliptical
- .07 - Wall washer

- .01 - 10° Spot
- .36 - 25° Medium
- .32 - 45° Wide
- .38 - 10°x40° Elliptical
- .07 - Wall washer

- .01 - 10° Spot
- .36 - 25° Medium
- .32 - 45° Wide
- .38 - 10°x40° Elliptical
- .07 - Wall washer

## Technical drawing

