

# Line

RECESSED LIGHT  
White led  
Diffused reflector



**Collection name**

**LINE 535 mm**

**LINE 970 mm**

**LINE 1270 mm**

**Technical data**

Power (Real data)	15.5 W	31.0 W	45.0 W
Lumen 3000K (Real data)	1378 lm (Optic .07)	2841 lm (Optic .07)	3995 lm (Optic .07)
Lumen 4000K (Real data)	1421 lm (Optic .07)	2756 lm (Optic .07)	4119 lm (Optic .07)
Class	I (Class II on request)	I (Class II on request)	I (Class II on request)
Nominal Voltage	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz
Power supply	Included	Included	Included
Max load (Alu version)	1000 kg (Alu, walk over)	1000 kg (Alu, walk over)	1000 kg (Alu, walk over)
Max load (Inox version)	1500 kg (Inox, walk over)	1500 kg (Inox, walk over)	1500 kg (Inox, walk over)

**Configuration code**

**Select finish / led / optic**

**10630 + X + Y + Z**

**10631 + X + Y + Z**

**10632 + X + Y + Z**

Finish **X**

- 6 - Inox Aisi 316L
- 4 - Grey (RAL 9006)

- 6 - Inox Aisi 316L
- 4 - Grey (RAL 9006)

- 6 - Inox Aisi 316L
- 4 - Grey (RAL 9006)

Color LED **Y**

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

- .2 - 2700K CRI > 80
- .3 - 3000K CRI > 80
- .4 - 4000K CRI > 80

Optic **Z**

- .07 - Wall washer
- .27 - Symmetric

- .07 - Wall washer
- .27 - Symmetric

- .07 - Wall washer
- .27 - Symmetric

**Technical drawing**

