

















# quantum range



	1,5 W	2 W	4 W	6 W	10 W	15 W	25 W
<b>_R</b> 	Ø 18 mm	Ø 24 mm	Ø 35 mm	Ø 42 mm	Ø 60 mm	Ø 83 mm	Ø 135 mm
<b>_RJ</b> 	-	Ø 50 mm	Ø 50 mm	Ø 55 mm	Ø 70 mm	Ø 80 mm	-
<b>Accessories</b>	-	 (RJ)					
<b>Finish</b>							
<b>Balance CRI 92</b>	2700K 3000K	2700K 3000K	2700K 3000K 4000K	2700K 3000K 4000K	2700K 3000K 4000K	2700K 3000K 4000K	2700K 3000K 4000K
<b>Efficiency CRI 80</b>	2700K 3000K 4000K	2700K 3000K 4000K	2700K 3000K 4000K	2700K 3000K 4000K	2700K 3000K 4000K	2700K 3000K 4000K	2700K 3000K 4000K
<b>Optics</b>	Medium Flood	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood
<b>Driver</b>	On/Off 1-10 V DALI	On/Off 1-10 V DALI	On/Off 1-10 V DALI	On/Off 1-10 V DALI	On/Off 1-10 V DALI	On/Off 1-10 V DALI	On/Off 1-10 V DALI
	15 mm	20 mm (_R) 44 mm (_RJ)	29 mm (_R) 44 mm (_RJ)	35 mm (_R) 49 mm (_RJ)	52 mm (_R) 64 mm (_RJ)	72 mm (_R) 73 mm (_RJ)	125 mm