



6 W DC

Anod. Al.	93690	2700K	703 lm	M	Narrow Spot	08
3 LEDs		3000K	703 lm	W	Medium Flood	20
		4000K	749 lm	N	Flood	50
					Wide Flood	90
					Elliptic	25
					Asymmetric	07

Electronics

<p>99179 ON/OFF 1 - 2 art.</p>	<p>99186 ON/OFF 2 - 4 art.</p>
---	---

12 W DC

Anod. Al.	93691	2700K	1406 lm	M	Narrow Spot	08
6 LEDs		3000K	1406 lm	W	Medium Flood	20
		4000K	1498 lm	N	Flood	50
					Wide Flood	90
					Elliptic	25
					Asymmetric	07

Electronics

<p>99179 ON/OFF 1 art.</p>	<p>99186 ON/OFF 1 - 2 art.</p>
---	---

18 W DC

Anod. Al.	93755	2700K	2109 lm	M	Narrow Spot	08
9 LEDs		3000K	2109 lm	W	Medium Flood	20
		4000K	2247 lm	N	Flood	50
					Wide Flood	90
					Elliptic	25
					Asymmetric	07

Electronics

<p>99186 ON/OFF 1 art.</p>

24 W DC

Anod. Al.	93785	2700K	2812 lm	M	Narrow Spot	08
12 LEDs		3000K	2812 lm	W	Medium Flood	20
		4000K	2996 lm	N	Flood	50
					Wide Flood	90
					Elliptic	25
					Asymmetric	07

Electronics

<p>99186 ON/OFF 1 art.</p>

Steel fixing brackets

	46-67 mm 98949
	90 mm 89045
	150 mm 89046
	300 mm 89047

Anti-glaring accessory

	366 mm 98782
	630 mm 98783
	930 mm 98784
	1230 mm 98785