
Versatility for every solution

Rubber is available with polyurethane covering for standard applications with temperatures between -20°C and +45°C. Available in two versions, 2D and 3D bend, to adapt to any design needs. The Rubber range includes numerous accessories, including recessed casings and clips to fasten the strips, both in the versions with or without wire hole.

The option with wire hole allows the power cable to be concealed from view, preserving its integrity. The space also becomes useful for running other wires. The small, toothed clips retain the flexible polyurethane body of the strip, allowing routing variations.



Customisation

In addition to the proposed dimensions, the length of the strip can be customised upon request. The custom version is sealed in the factory with the same procedure as the standard models in order to ensure the same production quality.

The customer can also cut the standard 3D bend (every 45 mm) and 2D bend (every 50 mm) version and seal the cut end using the special 99539 KIT, sold separately, maintaining the original product warranty.



3D bend

Rubber is one of a kind. Its new, patented internal circuit structure means the strip can be bent in any direction, creating a whole new spectrum of applications. The five-metre rolls can easily be cut every 45 millimetres for maximum versatility.



Maximum reliability and performance

The unit is UV stabilised to protect it from the sun, with IP67 and IK10 ratings and high standards of electrical, thermal and mechanical safety complying with EN 60598-1.

This, combined with its exceptional output of 1,100 lm/m, means that Rubber is second to none when it comes to performance and reliability.

