



Designer: Serge & Robert Cornelissen

NARRO 3400 1L



IK 08

Code LL2907.MWMO300EN

Description

Linear fixture with direct emission, single or bi-emission. The simple but harmonious and geometric design of the fixture allows to be used in both residential and professional environments. Visual comfort is guaranteed by the recessed optic while maintaining high performance. The large finish availability makes it versatile in different design contexts.

Constructive & Dimensional

Construction material	Aluminum
External screws	Stainless Steel A4
Length [mm]	3430
Width [mm]	39
Height [mm]	92

Electrical

Description	1 x 105 W LED 3000 K CRI>85 15000 lm
Operating Power	220-240 V / 50-60 Hz
Number of heads	1
Number of circuits	1
Driver positioning	Integral
Cord length [m]	2.5

Optical

Beam type	Suspension [21°-40°] medium
Light distribution	Direct lighting
Beam directionability	Fixed
Diffuser material	Polycarbonate
Diffuser finish	Opal

Lighting Source

Light source	LED
Power [W]	105 W
ZVEI - Led Type	LED
Color temperature	3000 K
Color rendering index	CRI>85
Nominal LED emission [Lm]	15000 lm
Light source	Included
Ambient temperature operating range [°C]	-20 °C ÷ +35 °C

Finish Code

.01 White (matt)