

Eolo



Eolo

Segnapasso LED per interni ed esterni.
Indoor/Outdoor LED footlight.

Led : 3000°K (W), 4000°K (N)

Optic : 80°

VO (alimentazione I voltage input) :

700mA corrente continua I constant current (CC)

220-240Vac (HI) (alimentazione con cassaforma per muratura
driver for brick wall-box)



Potenza I Power 3W - 700mA I 220/240Vac

Flusso Nominale I Total Efficiency Lm 375 (W) I 426 (N)

finitura I finishes	cod.	+ Led	+ Opt	+ VO
Palladio Lucido I Shining Palladium*	30428 __	W	80	CC
Rame Naturale I Natural Copper	30434 __	N		HI
Zinco I Zinco	30437 __			

Collegamento in serie I Serial connection

- Su tutte le finiture naturali su richiesta possibilità di trattamento antiossidante (antirvecchiamento)
On all natural finishes possibility on request of antioxiide treatment (everbright finish)

* Finiture indicate per installazioni in interno
Finishes suitable for indoor installation

Alimentatori vedi pag. Accessori e Alimentatori
Transformers see page Accessories and Transformers




Optional: cassaforma I wall-box
per/for driver 220/240Vac (HI)



kg 0,28


IP 65

DIMENSIONI I DIMENSIONS




FOTOMETRIE I PHOTOMETRIC DIAGRAMS


EOLO - 3W - 80°
h: 25cm



SISTEMA DI FISSAGGIO I FIXING SYSTEM



cassaforma kit incasso
220/240V
wall-box recessed kit
220/240V



Non prevede particolari predisposizioni (solo foratura per tasselli e fissaggio con viti)
It doesn't foresee particular predisposition (only perforation for wedges and fixing with screw)

INC/S