




LA STAGNA 2.0

Apparecchio LED lineare IP65 per installazione singola o in fila continua. Corpo e testate in policarbonato bianco, schermo coestruso in policarbonato opale rigato.


Alimentazione elettronica 220-240V 50-60Hz integrata, 2 pressacavi per la continuità di linea, terminale per installazioni stand-alone o per chiusura di fila continua e 2 staffe in acciaio armonico per installazione a parete o plafone inclusi. Cavo di alimentazione non incluso, da prevedere con guaina esterna D=5-8 mm.

Linear LED IP65 fixture for stand alone installation or in series system. Body and end caps in white polycarbonate, screen co-extruded polycarbonate opal lined. Electronic power supply 220-240V 50-60Hz integrated, no.2 cord grips for the continuity of line, an appropriate terminal suitable for stand-alone or for closing a continuous line and no.2 brackets for ceiling or wall mounting included. Power cable with outer sheath D=5-8 mm not included.



POWER	L (mm)	FLUX	4000K <input type="checkbox"/>
38W	1225	3810 lm	19401.01
48W	1525	4785 lm	19402.01

ACCESSORI ACCESSORIES



SOSPENSIONE IN ACCIAIO
REGOLABILE (1 pz.)
prevedere n.2 sospensioni per ogni
apparecchio.

ADJUSTABLE SUSPENSIONS (1 pc)
necessary No.2 suspensions for
each appliance.

CODE	L (mm)
18754.99	1200
18755.99	3000

